


RANGE	MODEL	CAPACITY	PAYLOAD	FINISH	HEIGHT	WIDTH	DEPTH
SP	SP150	149 litres	180kg	Powder Coated	890mm	910mm	910mm
SP	SP400	302 litres	405kg	Powder Coated	1070mm	1070mm	1070mm
SP	SP500	350 litres	480kg	Powder Coated	1150mm	1200mm	1200mm
SP	SP500 PG	350 litres	480kg	Galvanised Frame/Polyethylene Hopper	1150mm	1200mm	1200mm
SR/S	SR/S 610	600 litres	780kg	Powder Coated	960mm	1300mm	1300mm
SR/S	SR/S 610 PG	600 litres	780kg	Galvanised Frame/Polyethylene Hopper	960mm	1300mm	1300mm
SR/S	SR/S 810	800 litres	1000kg	Powder Coated	1030mm	1400mm	1400mm
SR/S	SR/S 810 PG	800 litres	1000kg	Galvanised Frame/Polyethylene Hopper	1130mm	1530mm	1530mm
SR/S	SR/S 1250 PG	1250 litres	1000kg	Galvanised Frame/Polyethylene Hopper	1350mm	1530mm	1530mm
SR/DD	SR/DD 550	500 litres	650kg	Powder Coated	800mm	1500mm	1100mm
SR/DD	SR/DD 950	900 litres	1150kg	Powder Coated	1100mm	1500mm	1100mm
SR/DD	SR/DD 1300	1300 litres	1150kg	Powder Coated Frame/Poly-Steel Hopper	1270mm	1500mm	1100mm
TORNADO	Tornado 1300	1300 litres	1340kg	Galvanised Frame/Polyethylene Hopper	1190mm	2300mm	1300mm
SQTF	SQTF 400	400 litres	480kg	Powder Coated Frame/Fibreglass Hopper	930mm	1100mm	1100mm
SQTF	SQTF 600	530 litres	640kg	Powder Coated Frame/Fibreglass Hopper	970mm	1510mm	1510mm
SQTF	SQTF 800	820 litres	948kg	Powder Coated Frame/Fibreglass Hopper	1090mm	1510mm	1510mm
SQTF	SQTF 1000	1000 litres	1200kg	Powder Coated Frame/Fibreglass Hopper	1190mm	1510mm	1510mm

optional  
extras




hydraulic remote  
ALL MODELS EXCEPT SP



agitator stirrer  
ALL MODELS EXCEPT  
SR/DD & TORNADO



cable remote  
ALL MODELS EXCEPT  
SQTF & TORNADO



side discharge chute  
SP, SR/S & SR/DD RANGE ONLY



four row discharge kit  
SP & SR/S RANGE ONLY



cover  
ALL MODELS

# AgriQuip

AGRICULTURAL IMPLEMENT WHOLESALERS



spreadmaster tornado 1300

spreadmaster  
3 point linkage  
spreaders

The “Spreadmaster”, tractor 3 point linkage mounted spreader range, will have a model to suit your expectations, and operation.

From a simple, single spinner model, to either of the precision, twin spinner or pendulum machines for greater accuracy.



BUILT TO LAST!

FOR YOUR NEAREST DEALER  
PHONE (06) 759 8402





## Model SP

**3 sizes: SP150, SP400, SP500**

- Single spinner spreader
- Powder coated frame and hopper
- Stainless steel wings and twin shutters
- Oil filled gearbox
- 6 – 14 m spreading width



## Model SP PG

**1 size: SP500PG**

- Single spinner spreader
- Hot dipped galvanised frame/polyethylene hopper
- Stainless steel wings and twin shutters
- Oil filled gearbox
- 6 – 14 m spreading width



## Model SR/S PG

**3 sizes: SR/S 610 PG  
SR/S 810 PG  
SR/S 1250 PG**

- Single spinner spreader
- Hot dipped galvanised frame/polyethylene hopper
- Stainless steel wings and twin shutters
- Oil filled gearbox
- 8 – 18 m spreading width



## Model SRS

**2 sizes: SRS/610  
SRS/810**

- Single spinner spreader
- powdercoated frame and hopper
- Stainless steel wings and shutters
- Oil filled gearbox
- 8 – 18 m spreading width

## Model SR/DD

**3 sizes: SR/DD 550, SR/DD 950,  
SR/DD 1300**

- Twin spinner spreader
- Powder coated frame and hopper (Polyethylene hopper extension on model 1300)
- Stainless steel wings and twin shutters
- Three oil filled gearboxes
- 8 – 18 m spreading width



## Model SQTF

**4 sizes: SQTF 400, SQTF 600,  
SQTF 800, SQTF 1000**

- Pendulum action spreader
- Hot dipped galvanised frame/fiberglass hopper
- Oil filled oscillating gearbox
- 5 – 14 m spreading width



## Model Tornado

**1 size: Tornado 1300**

- Twin spinner spreader
- Hot dipped galvanised frame and polyethylene hopper
- Stainless steel wings and shutters
- Three oil filled gearboxes
- 14 – 36m spreading width

