



3 Point Linkage Spreaders Brochure



SP Series

The Spreadmaster, tractor 3 point linkage mounted spreader range, will have a model to suit your expectations, and operations.



Model SP

3 sizes: SP150, SP400, SP500

- Single spinner spreader
- Powder coated frame and hopper
- Stainless steel wings and twin shutters
- Oil filled gearbox
- 6-14m spreading width



Model SP PG

1 size: SP500PG

- Single spinner spreader
- Hot dip galvanized frame/polyethylene hopper
- Stainless steel wings and twin shutters
- Oil filled gearbox
- 6-14m spreading width

Model	Capacity	Payload	Finish	Height	Width	Depth
SP150	149L	180kg	Powder Coated	890mm	910mm	910mm
SP400	302L	405kg	Powder Coated	1070mm	1070mm	1070mm
SP500	350L	480kg	Powder Coated	1150mm	1200mm	1200mm
SP500PG	350L	480kg	Galvanized frame/Polyethylene hopper	1150mm	1200mm	1200mm



SR/S Series



Model SR/S PG

3 sizes: SR/S610PG, SR/S820PG, SR/S1250PG

- Single spinner spread
- Hot dipped galvanized frame/polyethylene hopper
- Stainless steel wings and twin shutters
- Oil filled gearbox
- 8-18m spreading width

Model	Capacity	Payload	Finish	Height	Width	Depth
SR/S 610 PG	600L	780kg	Galvanized frame/Polyethylene hopper	960mm	1300mm	1300mm
SR/S 810 PG	800L	1000kg	Galvanized frame/Polyethylene hopper	1130mm	1530mm	1530mm
SR/S 1250 PG	1250L	1000kg	Galvanized frame/Polyethylene hopper	1350mm	1530mm	1530mm



SR/DD Series



Model SR/DD

3 sizes: SR/DD550, SR/DD950, SR/DD1300

- Twin spinner spreader
- Hot dipped galvanized frame (galvanized frame/polyethylene hopper extension on model 1300)
- Stainless steel wings and twin shutters
- Three oil filled gear boxes
- 8-18m spreading width

Model	Capacity	Payload	Finish	Height	Width	Depth
SR/DD550	500L	650kg	Hot dipped galvanized frame	800mm	1500mm	1100mm
SR/DD950	900L	1150kg	Hot dipped galvanized frame	1100mm	1500mm	1100mm
SR/DD1300	1300L	1150kg	Galvanized frame/Polyethylene hopper	1270mm	1500mm	1100mm



SQTF Series



Model SQTF

4 sizes: SQTF400, STQF600, STQF800, SQTF1000

- Pendulum action spreader
- Hot dipped galvanized frame/fibreglass hopper
- Oil filled oscillating gearbox
- 5-14m spreading width

Model	Capacity	Payload	Finish	Height	Width	Depth
SQTF400	400L	480kg	Hot dipped galvanized frame/Fibreglass hopper	930mm	1100mm	1100mm
SQTF600	530L	640kg	Hot dipped galvanized frame/Fibreglass hopper	970mm	1510mm	1510mm
SQTF800	820L	948kg	Hot dipped galvanized frame/Fibreglass hopper	1090mm	1510mm	1510mm
SQTF1000	1000L	1200kg	Hot dipped galvanized frame/Fibreglass hopper	1190mm	1510mm	1510mm



Tornado



Model Tornado

1 size: Tornado 1300

- Twin spinner spreader
- Hot dip galvanized frame and polyethylene hopper
- Stainless steel wings and shutters
- Three oil filled gearboxes
- 14-36m spreading width
- Highly accurate and precise
- Easily adjustable spreading vanes
- Simple and easy to remove hopper for cleaning
- Hydraulic remote shutter controls

Model	Capacity	Payload	Finish	Height	Width	Depth
T1300	1300L	1340kg	Galvanized frame/Polyethylene hopper	1190mm	2300mm	1300mm



30 Hurlstone Drive, New Plymouth

Phone: +64 6 759 8402

sales@agriquip.co.nz

www.agriquip.co.nz

